

SAFETY DATA SHEET

Eastern Chem-Lac

WB SOLAR CHEM BLACK - GALLON

Date Printed: 9/12/2022

Page 1 of 12

1. Product and Company Identification

Product Name : WB SOLAR CHEM BLACK - GALLON
Product Code : W3700-GL
Recommended Use: Please refer to Product Information/Technical Data Sheet.

Company Identification:

Eastern Chem-Lac
33 Haynes Circle
Chicopee, MA 01020

Information Phone: 413-592-4191
Emergency Phone: ChemTel 800-255-3924

2. Hazards Identification

EMERGENCY OVERVIEW

ASPIRATION HAZARD, CATEGORY 1
CARCINOGENICITY, CATEGORY 1

SIGNAL WORD:
WARNING



HAZARD STATEMENTS:
MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS
MAY CAUSE CANCER

PRECAUTIONARY STATEMENTS:
Do NOT induce vomiting.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.

Potential Health Effects

Eye:
May cause mechanical irritation.
Skin:
May cause mechanical skin irritation.
Ingestion:
Not hazardous in normal industrial use.
Inhalation:

SAFETY DATA SHEET

Eastern Chem-Lac

WB SOLAR CHEM BLACK - GALLON

Date Printed: 9/12/2022

Page 2 of 12

Not expected to cause effects from inhalation.

Chronic (Cancer) Information:

Contains Crystalline Silica. Long term overexposure to products containing Crystalline Silica may cause silicosis.

Crystalline Silica is listed as a carcinogen by the NTP and IARC. Contains CARBON BLACK, which is listed by the IARC as a Group 2B (possibly carcinogenic to humans). Not listed as a carcinogen by NTP, ACGIH, OSHA or the European Union.

There are no known human carcinogenic effects related to the PAH content in carbon blacks. Recent research has shown that the PAH content of carbon blacks is not released in biological fluids and thus not available for biological activity.

IARC: A component of this product present at levels greater than or equal to 0.1% is identified as a probable, possible or confirmed human carcinogen by IARC.

ACGIH: A component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP: A component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Teratology (Birth Defects) Information:
INFORMATION NOT AVAILABLE.

Reproduction Information:
INFORMATION NOT AVAILABLE.

Aggravation of Pre-Existing Conditions:
INFORMATION NOT AVAILABLE.

3. Composition/Information on Ingredients

Component	CAS#	% by Wt.
* 2-BUTOXY ETHANOL	111-76-2	9
ACGIH TLV: 20 PPM TWA		
OSHA PEL: 50 PPM TWA (SKIN)		
OSHA VPEL: 25 PPM TWA (SKIN)		
TALC	14807-96-6	7
OSHA: 2 MG/M3		
ACGIH: 2 MG/M3		
SILICA GEL	63231-67-4	6
ACGIH TLV: 10 MG/M3 TWA		
OSHA PEL: 6 MG/M3 TWA		

SAFETY DATA SHEET

Eastern Chem-Lac

WB SOLAR CHEM BLACK - GALLON

Date Printed: 9/12/2022

Page 3 of 12

# CRYSTALLINE SILICA (QUARTZ)	14808-60-7	5.1
ACGIH TLV: 0.05 MG/M3 TWA		
OSHA PEL: (10 MG/M3/(% SILICA +2)) TWA		
* N-BUTANOL	71-36-3	5
ACGIH: 50 PPM "SKIN" TWA		
OSHA: 50 PPM CEILING		
SILICON DIOXIDE	112926-00-8	3
ACGIH: 10 MG/M3 TWA, TOTAL DUST		
OSHA: 20 MPPCF3 TWA		
DIMETHYL ETHANOL AMINE	108-01-0	1
SUPPLIER: 10 MG/M3 TWA		
1,2-PROPYLENE GLYCOL	57-55-6	1
AIHA WEEL: 10 MG/M3 TWA aerosol only		
AIHA WEEL: 50 PPM TWA total		
# CARBON BLACK	1333-86-4	1.028
ACGIH: 3.5 MG/M3 TWA		
OSHA: 3.5 MG/M3 TWA		

4. First Aid Measures

Eyes:

Any material that contacts the eye should be washed out immediately with water. Flush with water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention if symptoms persist.

Skin:

Wash with soap and water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.

Ingestion:

Do NOT induce vomiting. Drink 1 or 2 glasses of milk or water to dilute. Call a poison control center or get medical attention immediately. Never give anything by mouth to an unconscious person.

Inhalation:

If symptomatic, move to fresh air. Get medical attention if symptoms persist.

Note to Physicians:

INFORMATION NOT AVAILABLE.

5. Fire Fighting Measures

Flammable Properties:

Flash Point: > 200 F

Method:

Explosive Limits:

Lower explosive limit: 1.1

Upper explosive limit: 12.6

Autoignition Temperature:

INFORMATION NOT AVAILABLE.

SAFETY DATA SHEET

Eastern Chem-Lac

WB SOLAR CHEM BLACK - GALLON

Date Printed: 9/12/2022

Page 4 of 12

Hazardous Combustion Products:

INFORMATION NOT AVAILABLE.

Extinguishing Media:

Waterbased material will not burn until all water has boiled away. Residual solids and/or product container may support combustion. Use water, foam, dry chemical or CO2.

Firefighting Procedures:

Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective clothing.

Unusual Fire and Explosion Hazards: High temperatures can cause sealed containers to rupture due to a build up of internal pressure. Cool with water spray.

6. Accidental Release Measures

Small Spill:

See Information for Large Spill, below:

Large Spill:

Use personal protective equipment. Ensure adequate ventilation.

Environmental Precautions:

Methods/Materials for Containment and Cleaning Up:

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/state/federal regulations.

7. Handling and Storage

Handling:

Store in a cool, dry, well ventilated area. Keep containers tightly closed.

EMPTY CONTAINER PRECAUTIONS: Attention! This container is hazardous when empty. Follow label warnings even after container is emptied since empty containers may retain product residues. Do not re-use empty container without professional cleaning for food, clothing or products. for human or animal consumption or where skin contact can occur.

Storage:

Prevent unauthorized access.

Store in a well ventilated place.

Keep container tightly closed.

Keep cool.

8. Exposure Controls/Personal Protection

SAFETY DATA SHEET

Eastern Chem-Lac

WB SOLAR CHEM BLACK - GALLON

Date Printed: 9/12/2022

Page 5 of 12

Airborne Exposure Limits:

SEE SECTION 3 FOR THIS INFORMATION

Engineering Controls:

Ventilation: Good general ventilation (typically 10 air changes per hour) should be used.

Ventilation rates should be matched to conditions.

Ventilation should be explosion proof.

Supplementary local exhaust ventilation, closed systems, or respiratory protection may be needed in special circumstances such as poorly ventilated spaces, spray painting, mechanical generation of dusts, heating, drying, etc.

Personal Protective Equipment

Respiratory Protection:

If engineering controls do not maintain airborne concentrations to an acceptable level, an approved respirator must be

worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance

with OSHA Standard 63 CFR 1152, January 8, 1998. Respirator type: Organic Vapor.

Skin Protection:

Wear impervious gloves to prevent skin contact.

Recommended Decontamination Facilities: eye bath, washing facilities, safety shower.

Eye Protection:

Chemical safety goggles or glasses with side shields.

9. Physical and Chemical Properties

Boiling Point: 212 F

Freezing Point: 32 F

Vapor Pressure:

NO INFORMATION AVAILABLE

Vapor Density:

HEAVIER THAN AIR

Solubility in Water:

SOLUBLE

Evaporation Rate: SLOWER THAN ETHER

Specific Gravity: 1.149

pH Range: 8-10

Coating VOC: 2.55 lb/g1

SAFETY DATA SHEET

Eastern Chem-Lac

WB SOLAR CHEM BLACK - GALLON

Date Printed: 9/12/2022

Page 6 of 12

Material VOC: 1.6 lb/gl

Odor:

Mild acrylic odor.

Appearance:

Liquid.

Partition Coefficient:

INFORMATION NOT AVAILABLE.

10. Stability and Reactivity

Chemical Stability (Conditions to Avoid):

Stable under normal storage/use conditions.

Incompatibility:

Avoid strong oxidizing agents, acids and alkalies.

Hazardous Decomposition Products:

Smoke, soot and carbon dioxide, carbon monoxide.

Hazardous Polymerization:

Will not occur under normal conditions.

11. Toxicological Information

Eye Irritation/Damage:

Component 108-01-0:

Eye irritation, Category 1

Component 57-55-6:

May cause slight temporary eye irritation.

Component 71-36-3:

Moderate eye irritation, Category 2

Skin Irritation/Damage:

Component 108-01-0:

LD50: 1100 mg/kg, rat. Category 4

Extremely corrosive to skin, Category 1B

Component 57-55-6:

LD50: >2000 mg/kg, rat. Not categorized.

Component 71-36-3:

LD50: 3,400 mg/kg, rabbit. Not categorized.

Mild skin irritant, category 2

Acute Oral Toxicity:

Component 108-01-0:

LD50: 1183 mg/kg, rat. Category 4

Component 57-55-6:

SAFETY DATA SHEET

Eastern Chem-Lac

WB SOLAR CHEM BLACK - GALLON

Date Printed: 9/12/2022

Page 7 of 12

LD50: >20,000 mg/kg, rat. Not categorized.

Component 1333-86-4:

LD50: >8000 mg/kg, rat. Category 5

Component 14808-60-7:

LD50: >5000 mg/kg, rat. Category 5

Component 71-36-3:

LD50: 790 mg/kg, rat. Category 4

Component 111-76-2:

LD50: 1300 mg/kg, rat. Category 4

Acute Inhalation Toxicity:

Component 108-01-0:

LC50: 6 mg/l, rat. Category 3

Component 57-55-6:

LC50: 317 mg/l, rat. Not categorized.

Component 71-36-3:

LC50: 8000 ppm, rat. Category 4

Respiratory/Skin Sensitization:

Component 108-01-0:

No evidence of respiratory or skin sensitization.

Component 57-55-6:

No evidence of respiratory or skin sensitization.

Component 71-36-3:

No evidence of respiratory or skin sensitization.

Carcinogenicity:

Component 108-01-0:

Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH

Component 57-55-6:

Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH

Component 1333-86-4:

Listed by IARC as a group 2B carcinogen (possibly carcinogenic to humans).

Carbon Black is not listed as a carcinogen by

NTP, OSHA or ACGIH. GHS Category 2.

Component 14808-60-7:

Listed by IARC as a group 1 carcinogen (carcinogenic to humans), and as a known carcinogen by NTP. GHS Category 1A.

Component 71-36-3:

Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH

Reproductive Toxicity:

Component 108-01-0:

No evidence of human reproductive toxicity.

SAFETY DATA SHEET

Eastern Chem-Lac

WB SOLAR CHEM BLACK - GALLON

Date Printed: 9/12/2022

Page 8 of 12

Component 57-55-6:
No evidence of human reproductive toxicity.
Component 71-36-3:
No evidence of human reproductive toxicity.

Germ Cell Mutagenicity:

Component 108-01-0:
No data

Component 57-55-6:
No evidence of human developmental toxicity.
Component 71-36-3:
No data

Aspiration Toxicity:

Component 108-01-0:
Not classified as an Aspiration Hazard.

Component 57-55-6:
Not classified as an Aspiration Hazard.
Component 71-36-3:
Not classified as an Aspiration Hazard.
Component 111-76-2:
Aspiration Hazard; Category 1

STOT-single exposure:

Component 108-01-0:
Transient target organ effects (Category 3);
Respiratory tract irritation.

Component 57-55-6:
No data
Component 71-36-3:
May cause respiratory irritation. May cause drowsiness or dizziness.
Component 111-76-2:
No data

STOT-repeated exposure:

Component 108-01-0:
No data

Component 57-55-6:
In rare cases, repeated excessive exposure to propylene glycol may cause central nervous system effects.
Component 71-36-3:
No data
Component 111-76-2:
No data

SAFETY DATA SHEET

Eastern Chem-Lac

WB SOLAR CHEM BLACK - GALLON

Date Printed: 9/12/2022

Page 9 of 12

Routes of Exposure:

Inhalation of vapors, skin/eye/mucous membrane absorption, ingestion.

INFORMATION NOT AVAILABLE.

12. Ecological Information

Environmental Toxicity:

Component 108-01-0:

LC50: 146.63 mg/l (fish); EC50: 98.37 mg/l (daphnia); EC50: 66.08 mg/l (algae)

Component 57-55-6:

LC50: 40,613 mg/l (fish); EC50: 18,340 mg/l (daphnia); EC50: 19,000 mg/l (algae)

Component 1333-86-4:

LC50: <1000 mg/l (fish); EC50: <5600 mg/l (daphnia); EC50: <10,000 mg/l (algae)

Component 71-36-3:

LC50: >100 mg/l (fish); EC50: >100 mg/l (daphnia)

Persistence & degradability:

Component 108-01-0:

Readily biodegradable

Component 57-55-6:

Readily biodegradable

Component 1333-86-4:

Carbon Black is essentially elemental carbon & cannot be further biodegraded by microorganisms.

Component 71-36-3:

This material is expected to be readily biodegradable.

Bioaccumulative Potential:

Component 108-01-0:

Does not bioaccumulate

Component 57-55-6:

Bioconcentration potential is low (BCF < 100 or Log Pow <3).

Component 1333-86-4:

Not expected to bioaccumulate.

Component 71-36-3:

Not expected to significantly bioaccumulate

Mobility in soil:

Component 108-01-0:

No data

Component 57-55-6:

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process. Potential for mobility in soil is very high. (Koc between 0 and 50).

SAFETY DATA SHEET

Eastern Chem-Lac

WB SOLAR CHEM BLACK - GALLON

Date Printed: 9/12/2022

Page 10 of 12

Component 71-36-3:

When released into the soil, this material is expected to leach into groundwater.

Other Adverse Ecological Effects:

No information

Component 108-01-0:

Harmful to aquatic life

Component 57-55-6:

Material is practically non-toxic to aquatic organisms on an acute basis.

13. Disposal Considerations

Waste Disposal Method:

Discharge, treatment or disposal is subject to national, state, or local laws. The toxicity characteristic (TC) has not been evaluated by the Toxicity Characteristic Leaching Procedure (TCLP). Federal Regulations may apply to empty container. State and/or local regulations may be different.

Of the methods of disposal currently available, it is recommended that an alternative be selected according to the following order of preference, based upon environmental acceptability: (1) recycle or rework, if feasible; (2) incinerate at an authorized facility; or (3) treat at an acceptable waste treatment facility.

Be sure to contact the appropriate government environmental agencies if further guidance is required.

Contaminated Materials:

INFORMATION NOT AVAILABLE.

14. Transport Information

SAFETY DATA SHEET

Eastern Chem-Lac

WB SOLAR CHEM BLACK - GALLON

Date Printed: 9/12/2022

Page 11 of 12

Domestic (Land, DOT), International (Water, IMO/IMDG), International (Air, ICAO)
Road and Rail (ADR/RID), Air (ICAO/IATA), Vessel (IMO/IMDG):

DOT (USA) Shipping Name: Not regulated by DOT/IATA/IMDG

UN/NA ID No: Not regulated by DOT/IATA/IMDG

Hazard Class: Not regulated by DOT/IATA/IMDG

Packing Group: Not regulated by DOT/IATA/IMDG

UN Number:

UN Shipping Name:

INFORMATION NOT AVAILABLE.

Transport Hazard Class:

Packing Group:

Environmental Hazards:

INFORMATION NOT AVAILABLE.

Marine Pollutant:

Components of this product do not appear on the list of Marine Pollutants (49CFR 172.101)

Special Precautions for User:

INFORMATION NOT AVAILABLE.

15. Regulatory Information

U.S. Federal Regulations:

TSCA: All components of this material are on the
US TSCA 8(b) Inventory or are exempt from listing.

OSHA:

This product is hazardous under OSHA's Hazard Communication Std. Not regarded
as a health hazard under current
legislation.

CERCLA: SARA Hazard Category:

INFORMATION NOT AVAILABLE.

Section 313:

"*" Indicates toxic chemical(s) subject to the reporting requirements of
section 313 of Title III and of 40 CFR 372.

International Regulations:

Canadian WHMIS:

INFORMATION NOT AVAILABLE.

Canadian Environmental Protection Act (CEPA):

INFORMATION NOT AVAILABLE.

EINECS:

INFORMATION NOT AVAILABLE.

State Regulations:

"#" Indicates a chemical known to the state of California to cause cancer, birth
defects or other reproductive harm.

SAFETY DATA SHEET

Eastern Chem-Lac

WB SOLAR CHEM BLACK - GALLON

Date Printed: 9/12/2022

Page 12 of 12

Volatile Organic Compounds:

COATING VOC content is being expressed as mass of VOC per unit volume of coating less water and exempt solvents, where applicable.

MATERIAL VOC content is the actual weight of VOC per unit volume.

16. Other Information

Date Revised: 09/12/22

Prepared By: Regulatory Compliance

Information Contact: Regulatory Compliance 413-592-4191 ext 106

Manufacturer Disclaimer:

USERS RESPONSIBILITY: A bulletin such as this cannot be expected to cover all possible individual situations. As the user has the responsibility to provide a safe workplace, all aspects of an individual operation should be examined to determine if, or where, precautions - in addition to those described herein - are required. Any health hazard and safety information herein should be passed on to your customers or employees, as the case may be.

DISCLAIMER OF LIABILITY: The information contained herein is, to the best of our knowledge and belief, accurate.

However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards

which exist. Final determination of suitability of the chemical is the sole responsibility of the user. No

representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or any

other nature are made hereunder with respect to the information contained herein or the chemical to which the

information refers. These data relate only to the specific material designated herein and do not relate to use in

combination with any other material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.

End of Material Safety Data Sheet