



R1200 URACHEM REDUCER

GENERAL INFORMATION	PHYSICAL PROPERTIES	APPLICATION/DEFINITIONS
<p>Medium evaporator suitable for high solids and low solids urethanes..</p> <p>Eastern Chem Lac. warrants that its products meet its internal specifications and are of merchantable quality. However, the purchaser is solely responsible for the suitability of the product for any particular application. The purchaser should thoroughly test or qualify the product for serviceability, environmental compliance and health and safety factors prior to use. Further, our total liability is limited to the price of the product or replacement in kind.</p> <p>Eastern Chem Lac 33 Haynes Circle Chicopee, MA 01020 Phone: 413-592-6997 Fax: 413-594-7321 www.eclcoatings.com</p>	<ol style="list-style-type: none"> 1. VOC: 7.15 lbs/gallon 857 grams/liter) 2. Weight per gallon: 7.15 lbs/gallon 3. Evaporation Rate: 9 4. Solvent Strength: 8 5. Flow Time: 7 6. Set Up Time: 7 7. Shelf Life Two years from date of manufacture 	<p>To reduce urethanes to spraying viscosity. Before using with other systems, check for compatibility.</p> <p>Definitions: Evaporation Rate: Measure of the time in minutes required for 90% to evaporate. Solvent Strength: Ratings express the ability to dissolve resin and reduce viscosity. Rated 1 – 10 (10 being best) Flow Time: Good flow permits paint film to level out to a smooth film of uniform thickness without orange peel. Rated from 1 – 10 (10 being best). Set Up Time: Relative rating of time necessary to obtain surface or tack free drying of film. Rated from 1 – 10 (10 being best).</p> <p>Safety Precautions: This product is intended for professional use in an industrial environment only. Consult the Material Safety Data Sheet prior to application.</p>