

Eastern Chem-Lac, LLC
 33 Haynes Circle
 Chicopee, MA 01020
 Telephone 413-592-6997
 Facsimile: 413-594-7321



8D38 LOW VOC CAPE COD GREY ALKYD

GENERAL INFORMATION	PHYSICAL PROPERTIES	APPLICATION
<p>A high performance alkyd primer designed for use over raw lumber.</p> <p>This product has a fast dry time, excellent weatherability, good mold and mildew resistance, good flexibility and good stain blocking properties.</p> <p>Eastern Chem-Lac, LLC warrants that its products meet its internal specifications and are of merchantable quality. However, the purchaser is solely responsible for the suitability of the product for any particular application. The purchaser should thoroughly test or qualify the product for serviceability, environmental compliance and health and safety factors prior to use. Further, our total liability is limited to the price of the product or replacement in kind.</p> <p>Eastern Chem-Lac, LLC 33 Haynes Circle Chicopee, MA 01020 Phone: 413-592-6997 Fax: 413-594-7321 www.ecloatings.com</p>	<ol style="list-style-type: none"> 1. Color: Cape Cod Grey 2. Volume Solids: 58 +/- 2% 3. Solids by Weight: 78 +/- 2% 4. Viscosity: 19 seconds max. #3 Zahn 5. DFT: 2 – 4 mils dft 6. Theoretical Coverage @ 1 mil dft: 930 ft²/gallon 7. Gloss @ 60° 3 maximum 8. Dry Time Set to Touch: 2 hours max. To Recoat: Overnight 9. VOC 2.8 lbs/gallon (340 grams/liter)- maximum 	<p>Application Methods: Use conventional spray, airless spray or flowcoat.</p> <p>Surface must be clean and free of grease, dirt, oil, and other contaminants that could interfere with proper adhesion.</p> <p>Reduction: Reduce with Mineral Spirits as needed.</p> <p>Clean-up: Clean tools and equipment immediately after use with Mineral Spirits.</p> <p>Safety Precautions: This product is intended for professional use in an industrial environment only. Consult the Material Safety Data Sheet prior to application.</p>