

# SAFETY DATA SHEET

## *Eastern Chem-Lac*

LOW VOC CAPE COD GREY ALKYD-DRUM

Date Printed: 9/12/2023

Page 1 of 12

---

### 1. Product and Company Identification

---

Product Name : LOW VOC CAPE COD GREY ALKYD-DRUM

Product Code : 8D38-DR

Recommended Use: Please refer to Product Information/Technical Data Sheet.

Company Identification:

Eastern Chem-Lac  
33 Haynes Circle  
Chicopee, MA 01020

Information Phone: 413-592-4191

Emergency Phone: ChemTel 800-255-3924

### 2. Hazards Identification

---

EMERGENCY OVERVIEW

HAZARD CLASSIFICATION:

FLAMMABLE LIQUID, CATEGORY 3

ACUTE TOXICITY (ORAL), CATEGORY 5

SKIN IRRITATION, CATEGORY 2

EYE IRRITATION, CATEGORY 2B

CHRONIC TOXICITY, ASPIRATION HAZARD, CATEGORY 1

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE, CATEGORY 3 (CENTRAL NERVOUS SYSTEM)

CARCINOGENICITY, CATEGORY 1

SIGNAL WORD:

DANGER



# SAFETY DATA SHEET

## *Eastern Chem-Lac*

LOW VOC CAPE COD GREY ALKYD-DRUM

Date Printed: 9/12/2023

Page 2 of 12

---

### HAZARD STATEMENTS:

FLAMMABLE LIQUID AND VAPOR  
HARMFUL IF SWALLOWED  
CAUSES SKIN IRRITATION  
CAUSES EYE IRRITATION  
MAY CAUSE CANCER  
MAY CAUSE DROWSINESS OR DIZZINESS

### PRECAUTIONARY STATEMENTS:

Keep away from heat, sparks, open flame/hot surfaces.  
No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting and other equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Store/Use outdoors or in a well ventilated place.  
Keep cool.  
Store locked up.  
Wash hands thoroughly after handling.  
Do not eat or drink while using this product.  
Do not breathe vapors.  
If inhaled: Remove person to fresh air and keep comfortable for breathing.  
If swallowed, immediately call a poison control center.  
Rinse mouth.  
Wear protective gloves, protective clothing, eye/face protection.  
If on skin or hair: Take off immediately all contaminated clothing. Rinse skin with water/shower.  
If skin irritation occurs, seek medical advice.  
Take off contaminated clothing and wash it before reuse.  
If exposed or concerned, get medical advice or attention.  
Call a poison center or doctor if you feel unwell.  
If in eyes, rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: get medical attention.  
In case of fire: Use dry chemical, CO<sub>2</sub>, Halon or foam to extinguish.  
Dispose of contents/container in accordance with all local, regional, national regulations.  
Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.

### Potential Health Effects

#### Eye:

Can cause eye irritation.

#### Skin:

Causes skin irritation.

#### Ingestion:

# SAFETY DATA SHEET

## *Eastern Chem-Lac*

LOW VOC CAPE COD GREY ALKYD-DRUM

Date Printed: 9/12/2023

Page 3 of 12

If swallowed, call a poison control center or physician if you feel unwell.  
Rinse mouth.

Inhalation:

May cause drowsiness or dizziness.

Chronic (Cancer) Information:

Contains Crystalline Silica. Long term overexposure to products containing Crystalline Silica may cause silicosis.

Crystalline Silica is listed as a carcinogen by the NTP and IARC.

IARC: A component of this product present at levels greater than or equal to 0.1% is identified as a probable, possible or confirmed human carcinogen by IARC.

ACGIH: A component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP: A component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Teratology (Birth Defects) Information:

INFORMATION NOT AVAILABLE.

Reproduction Information:

INFORMATION NOT AVAILABLE.

Aggravation of Pre-Existing Conditions:

Dermititis or other skin conditions.

### **3. Composition/Information on Ingredients**

Component	CAS#	% by Wt.
PETROLEUM DISTILLATE	64742-47-8	20
ACGIH: 500 PPM - TWA		
OSHA: 500 PPM - TWA		
SUPPLIER: 200 PPM - TWA		
# TITANIUM DIOXIDE	13463-67-7	9.798
ACGIH: 10 MG/M3 TWA		
OSHA: 10 MG/M3 TWA		
TALC	14807-96-6	7
OSHA: 2 MG/M3		
ACGIH: 2 MG/M3		
MAGNESITE	546-93-0	5
OSHA: 5 MG/M3 (RESP DUST)		
ACGIH: 10 MG/M3 (RESP DUST)		
DIMETHYL CARBONATE	616-38-6	4
ACGIH TLV: NOT ESTABLISHED		

# SAFETY DATA SHEET

## *Eastern Chem-Lac*

LOW VOC CAPE COD GREY ALKYD-DRUM

Date Printed: 9/12/2023

Page 4 of 12

---

OSHA PEL: NOT ESTABLISHED  
SUPPLIER: 200 PPM (TWA)  
ALUMINUM SILICATE, HYDROUS 1332-58-7 1  
ACGIH: 0.1 MG/M3 RESPIRABLE CRYSTALLINE FRACTION  
# MICROCRYSTALLINE SILICA (QUARTZ) 14808-60-7 .181  
ACGIH TLV: 0.10 MG/M3  
ACGIH TLV: 0.05 MG/M3, RESPIRABLE FRACTION  
OSHA PEL: 0.10 MG/M3, RESPIRABLE DUST  
NIOSH: 0.05 MG/M3 TWA, RESPIRABLE DUST

### **4. First Aid Measures**

---

Eyes:  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Skin:  
If on skin: wash with plenty of soap & water. If skin irritation occurs: Get Medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Ingestion:  
If swallowed: Immediately call a poison center/physician.  
Do NOT induce vomiting.

Inhalation:  
If inhaled: Remove person to fresh air and keep comfortable for breathing.  
Call a poison control center/get medical attention if you feel unwell.

Note to Physicians:  
INFORMATION NOT AVAILABLE.

### **5. Fire Fighting Measures**

---

Flammable Properties:  
Flash Point: 105 F Method: TCC  
Explosive Limits:  
Lower explosive limit: 0.6  
Upper explosive limit: 12.9

Autoignition Temperature:  
INFORMATION NOT AVAILABLE.  
Hazardous Combustion Products:  
Smoke, soot and carbon dioxide, carbon monoxide.  
Extinguishing Media:

# SAFETY DATA SHEET

## *Eastern Chem-Lac*

LOW VOC CAPE COD GREY ALKYD-DRUM

Date Printed: 9/12/2023

Page 5 of 12

---

Dry chemical, CO2, Halon, Foam

Firefighting Procedures:

Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective clothing.

Unusual Fire and Explosion Hazards: High temperatures can cause sealed containers to rupture due to a build up of internal pressure. Cool with water spray. Vapors are heavier than air and can travel some distance away and flash back.

Sensitivity to Static Discharge: Material may accumulate a static charge which could act as an ignition source.

Precautions should be taken when pouring to minimize splash/free fall.

## **6. Accidental Release Measures**

---

Small Spill:

See Information for Large Spill, below:

Large Spill:

Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Environmental Precautions:

INFORMATION NOT AVAILABLE.

Methods/Materials for Containment and Cleaning Up:

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/state/federal regulations.

## **7. Handling and Storage**

---

Handling:

Keep away from heat, sparks, open flames, hot surfaces. NO SMOKING. Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/processing equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/eye protection/face protection.

Storage:

Prevent unauthorized access.

Store in a well ventilated place.

Keep container tightly closed.

Keep cool.

# SAFETY DATA SHEET

## *Eastern Chem-Lac*

LOW VOC CAPE COD GREY ALKYD-DRUM

Date Printed: 9/12/2023

Page 6 of 12

---

### **8. Exposure Controls/Personal Protection**

---

Airborne Exposure Limits:

SEE SECTION 3 FOR THIS INFORMATION

Engineering Controls:

Ventilation: Good general ventilation (typically 10 air changes per hour) should be used.

Ventilation rates should be matched to conditions.

Ventilation should be explosion proof.

Supplementary local exhaust ventilation, closed systems, or respiratory protection may be needed in special circumstances such as poorly ventilated spaces, spray painting, mechanical generation of dusts, heating, drying, etc.

Personal Protective Equipment

Respiratory Protection:

If engineering controls do not maintain airborne concentrations to an acceptable level, an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA Standard 63 CFR 1152, January 8, 1998. Respirator type: Organic Vapor.

Skin Protection:

Wear impervious gloves to prevent skin contact.

Recommended Decontamination Facilities: eye bath, washing facilities, safety shower.

Eye Protection:

Chemical safety goggles or glasses with side shields.

### **9. Physical and Chemical Properties**

---

Boiling Point: 194 F

Melting Point:

INFORMATION NOT AVAILABLE.

Freezing Point: n/a

Vapor Pressure:

Information not available for mixture

Vapor Density:

HEAVIER THAN AIR

Solubility in Water:

NEGLIGIBLE

Evaporation Rate: SLOWER THAN ETHER

# SAFETY DATA SHEET

## *Eastern Chem-Lac*

LOW VOC CAPE COD GREY ALKYD-DRUM

Date Printed: 9/12/2023

Page 7 of 12

---

Specific Gravity: 1.454

Weight per Gallon: 12.11 lb/gal

Coating VOC: 2.7 lb/gal

Material VOC: 2.56 lb/gal

Odor:

Mild solvent odor.

Appearance:

Liquid.

Partition Coefficient:

INFORMATION NOT AVAILABLE.

### **10. Stability and Reactivity**

---

Chemical Stability (Conditions to Avoid):

Stable under normal storage/use conditions.

Incompatibility:

Avoid strong oxidizing agents, acids and alkalies.

Hazardous Decomposition Products:

INFORMATION NOT AVAILABLE.

Hazardous Polymerization:

Will not occur under normal conditions.

### **11. Toxicological Information**

---

Eye Irritation/Damage:

Component 64742-47-8/64742-48-9:

Seriously irritating to eyes, Category 2A

Skin Irritation/Damage:

Component 64742-47-8/64742-48-9:

Causes Skin Irritation, Category 2

(4 hrs, Rabbit)

Acute Oral Toxicity:

Component 14808-60-7:

LD50: >5000 mg/kg, rat. Category 5

Component 64742-47-8/64742-48-9:

LD50: no data

Component 13463-67-7:

LD50: 10,000 mg/kg, rat. Category 5

Component 616-38-6:

LD50: >5000 mg/kg, rat. Category 5

Acute Inhalation Toxicity:

# SAFETY DATA SHEET

## *Eastern Chem-Lac*

LOW VOC CAPE COD GREY ALKYD-DRUM

Date Printed: 9/12/2023

Page 8 of 12

---

Component 64742-47-8/64742-48-9:  
No data

Respiratory/Skin Sensitization:  
Component 64742-47-8/64742-48-9:  
No data.

Carcinogenicity:  
Component 13463-67-7:  
Listed by IARC as a group 2B carcinogen (possibly carcinogenic to humans). GHS  
Category 2.

Component 14808-60-7:  
Listed by IARC as a group 1 carcinogen (carcinogenic to humans), and as a known  
carcinogen by NTP. GHS Category 1A.

Component 64742-47-8/64742-48-9:  
Not classifiable as a human carcinogen

Reproductive Toxicity:  
Component 64742-47-8/64742-48-9:  
Animal testing did not show any effects on fertility; (Teratogenicity):embryonic  
classification not possible from  
current data.

Germ Cell Mutagenicity:  
Component 64742-47-8/64742-48-9:  
Mutagenicity classification not possible from current data assessment.

Aspiration Toxicity:  
Component 64742-47-8/64742-48-9:  
Aspiration Hazard; Category 1  
Component 616-38-6:  
Not classified as an Aspiration Hazard.

STOT-single exposure  
Component 64742-47-8/64742-48-9:  
(Route: inhalation). May cause drowsiness or dizziness.  
Component 616-38-6:  
No data

STOT-repeated exposure  
Component 64742-47-8/64742-48-9:  
No data on Repeated Exposure effects



# SAFETY DATA SHEET

## *Eastern Chem-Lac*

LOW VOC CAPE COD GREY ALKYD-DRUM

Date Printed: 9/12/2023

Page 9 of 12

---

Component 616-38-6:

No data

Routes of Exposure:

Inhalation of vapors, skin/eye/mucous membrane absorption, ingestion.

## **12. Ecological Information**

---

Environmental Toxicity:

Component 64742-47-8/64742-48-9:

LL50: 10 mg/l (rainbow trout); EL50: 1.4 mg/l (daphnia);

EL50: 1 mg/l (algae)

Component 616-38-6:

LC50: 100 mg/l (fish); EC50: >100 mg/l (daphnia); EC50: >100 mg/l (algae)

Persistence & degradability:

Component 64742-47-8/64742-48-9:

Biodegradability: Aerobic

Biodegradation: 61% Exposure time: 28 d

Readily biodegradable

Component 616-38-6:

Readily biodegradable

Bioaccumulative potential:

Component 64742-47-8/64742-48-9:

No data.

Component 616-38-6:

No Data

Mobility in soil:

Component 64742-47-8/64742-48-9:

No data

Component 616-38-6:

No data

# SAFETY DATA SHEET

## *Eastern Chem-Lac*

LOW VOC CAPE COD GREY ALKYD-DRUM

Date Printed: 9/12/2023

Page 10 of 12

---

Other Adverse Ecological Effects:  
Component 616-38-6:  
Presumed non-toxic to aquatic life.

### **13. Disposal Considerations**

---

#### Waste Disposal Method:

Discharge, treatment or disposal is subject to national, state, or local laws. When a decision is made to discard this material as supplied, it meets RCRA's characteristic definition of ignitability. The toxicity characteristic (TC) has not been evaluated by the Toxicity Characteristic Leaching Procedure (TCLP). Federal Regulations may apply to empty container. State and/or local regulations may be different. Of the methods of disposal currently available, it is recommended that an alternative be selected according to the following order of preference, based upon environmental acceptability: (1) recycle or rework, if feasible; (2) incinerate at an authorized facility; or (3) treat at an acceptable waste treatment facility. Be sure to contact the appropriate government environmental agencies if further guidance is required.

### **14. Transport Information**

---

Domestic (Land, DOT), International (Water, IMO/IMDG), International (Air, ICAO) Road and Rail (ADR/RID), Air (ICAO/IATA), Vessel (IMO/IMDG):  
DOT (USA) Shipping Name: Not regulated by DOT, COMBUSTIBLE LIQUID\*  
UN/NA ID No: n/a  
Hazard Class: n/a  
Packing Group: n/a  
\*NOT REGULATED BY GROUND TRANSPORTATION IN NON-BULK PACKAGING (450L OR 119 GALLONS OR LESS) PER CFR 173.150 (f) (2).

#### IF SHIPPED BY AIR, VESSEL OR IN BULK THEN:

Shipping name: Paint  
UN/NA ID No: UN1263  
Hazard Class: 3  
Packing Group: III

# SAFETY DATA SHEET

## *Eastern Chem-Lac*

LOW VOC CAPE COD GREY ALKYD-DRUM

Date Printed: 9/12/2023

Page 11 of 12

---

Environmental Hazards:

INFORMATION NOT AVAILABLE.

Marine Pollutant:

Components of this product do not appear on the list of Marine Pollutants (49CFR 172.101)

Special Precautions for User:

INFORMATION NOT AVAILABLE.

### **15. Regulatory Information**

---

U.S. Federal Regulations:

TSCA: All components of this material are on the US TSCA 8(b) Inventory or are exempt from listing.

OSHA:

This product is hazardous under OSHA's Hazard Communication Std. Not regarded as a health hazard under current legislation.

CERCLA: SARA Hazard Category:

INFORMATION NOT AVAILABLE.

Section 313:

"\*" Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

International Regulations:

Canadian WHMIS:

INFORMATION NOT AVAILABLE.

Canadian Environmental Protection Act (CEPA):

INFORMATION NOT AVAILABLE.

EINECS:

INFORMATION NOT AVAILABLE.

State Regulations:

"#" Indicates a chemical known to the state of California to cause cancer, birth defects or other reproductive harm.

Volatile Organic Compounds:

COATING VOC content is being expressed as mass of VOC per unit volume of coating less water and exempt solvents, where applicable.

MATERIAL VOC content is the actual weight of VOC per unit volume.

### **16. Other Information**

---

Date Revised: 10/06/21

Prepared By: Eastern Chem-Lac

Information Contact: Eastern Chem-Lac, 413-592-4191

Manufacturer Disclaimer:

# SAFETY DATA SHEET

## *Eastern Chem-Lac*

LOW VOC CAPE COD GREY ALKYD-DRUM

Date Printed: 9/12/2023

Page 12 of 12

---

USERS RESPONSIBILITY: A bulletin such as this cannot be expected to cover all possible individual situations. As the user has the responsibility to provide a safe workplace, all aspects of an individual operation should be examined to determine if, or where, precautions - in addition to those described herein - are required. Any health hazard and safety information herein should be passed on to your customers or employees, as the case may be.

DISCLAIMER OF LIABILITY: The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Final determination of suitability of the chemical is the sole responsibility of the user. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or any other nature are made hereunder with respect to the information contained herein or the chemical to which the information refers. These data relate only to the specific material designated herein and do not relate to use in combination with any other material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.

End of Material Safety Data Sheet